



# Cat® Construction Forks

*The Construction Fork is an essential extension of your machine on the job site. Built tough to handle big loads, these forks lift and carry whatever you need moved on the job site. Part of the Fusion coupler system.*

## Load, Lift and Carry

- Larger-than-standard tines are rated for the kinds of work you need to do.
- Work efficiently on and off trucks, containers and loading docks.
- Rated for machine lifting capacities.
- Some models feature offset tines for improved visibility to the load.

## Built to Work for You

- You can select from maximum to minimum width – with 16 locking points for each tine.
- Choose what works best: tines up to 2348 mm (96 in) long are available.

- Tines can be unlocked to swing if needed, or left locked and unswinging – change when you need to.
- Compatible with any loader with a Fusion coupler – grab it when you need it. Drop it when you don't.

## Supported by Your Cat® Dealer

- Get machine for your forks, machine and everything in between from your local Cat dealer.
- Parts and support available anywhere you work...no matter how far around the world you go.

| Construction Forks       |       |        |       |        |       |        |       |        |       |        |  |
|--------------------------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|--|
| 2438 mm (96 in) Carriage |       |        |       |        |       |        |       |        |       |        |  |
|                          | mm    | in     | mm    | in     | mm    | in     | mm    | in     | mm    | in     |  |
| Tine Length              | 1219  | 48     | 1524  | 60     | 1830  | 72     | 2134  | 84     | 2438  | 96     |  |
| Tine Thickness           | 90    | 4      | 90    | 4      | 90    | 4      | 90    | 4      | 90    | 4      |  |
| Tine Width               | 180   | 7      | 180   | 7      | 180   | 7      | 180   | 7      | 180   | 7      |  |
| Carriage Height          | 4866  | 192    | 4866  | 192    | 4866  | 192    | 4866  | 192    | 4866  | 192    |  |
| Carriage Width           | 2528  | 99.5   | 2528  | 99.5   | 2528  | 99.5   | 2528  | 99.5   | 2528  | 99.5   |  |
| Minimum Tine Spacing     | 576   | 22.7   | 576   | 22.7   | 576   | 22.7   | 576   | 22.7   | 576   | 22.7   |  |
| Maximum Tine Spacing     | 2178  | 85.7   | 2178  | 85.7   | 2178  | 85.7   | 2178  | 85.7   | 2178  | 85.7   |  |
| Operating Weight         | 19212 | 42,343 | 19278 | 42,489 | 19339 | 42,623 | 19402 | 42,762 | 19464 | 42,899 |  |

| Construction Forks        |       |        |       |        |       |        |       |        |       |        |  |
|---------------------------|-------|--------|-------|--------|-------|--------|-------|--------|-------|--------|--|
| 2743 mm (108 in) Carriage |       |        |       |        |       |        |       |        |       |        |  |
|                           | mm    | in     | mm    | in     | mm    | in     | mm    | in     | mm    | in     |  |
| Tine Length               | 1219  | 48     | 1524  | 60     | 1830  | 72     | 2134  | 84     | 2438  | 96     |  |
| Tine Thickness            | 89    | 3.5    | 89    | 3.5    | 89    | 3.5    | 89    | 3.5    | 89    | 3.5    |  |
| Tine Width                | 180   | 7      | 180   | 7      | 180   | 7      | 180   | 7      | 180   | 7      |  |
| Carriage Height           | 4866  | 192    | 4866  | 192    | 4866  | 192    | 4866  | 192    | 4866  | 192    |  |
| Carriage Width            | 2833  | 111.5  | 2833  | 111.5  | 2833  | 111.5  | 2833  | 111.5  | 2833  | 111.5  |  |
| Minimum Tine Spacing      | 590   | 23.2   | 590   | 23.2   | 590   | 23.2   | 590   | 23.2   | 590   | 23.2   |  |
| Maximum Tine Spacing      | 2493  | 98.1   | 2493  | 98.1   | 2493  | 98.1   | 2493  | 98.1   | 2493  | 98.1   |  |
| Operating Weight          | 19265 | 42,343 | 19327 | 42,489 | 19389 | 42,623 | 19451 | 42,762 | 19514 | 42,899 |  |



# Cat® Construction Forks

| 96" Carriage Construction Fork  |                  |        |                  |        |                  |        |                  |        |                  |        |
|---|------------------|--------|------------------|--------|------------------|--------|------------------|--------|------------------|--------|
| Rated Load Firm & Level Ground (80% FTSTL) (Standard Configuration with Fusion) |                  |        |                  |        |                  |        |                  |        |                  |        |
|   | 48" Offset Tines |        | 60" Offset Tines |        | 72" Offset Tines |        | 84" Offset Tines |        | 96" Offset Tines |        |
|   | kg               | lb     | kg               | lb     | kg               | lb     | kg               | lb     | kg               | lb     |
| <sup>1</sup> Fork Capacity (Tine Rating × 2)                                    | 22200            | 48,952 | 17800            | 39,250 | 14800            | 32,634 | 12700            | 28,004 | 11300            | 24,916 |
| <sup>2</sup> 950 GC   | 6407             | 14,121 | 6064             | 13,365 | 5658             | 12,469 | 5002             | 11,024 | 4461             | 9,832  |
| <sup>2</sup> 950M   | 6700             | 14,768 | 6342             | 13,978 | 6014             | 13,254 | 5707             | 12,579 | 5423             | 11,953 |
| <sup>2</sup> 962M   | 7354             | 16,209 | 6976             | 15,375 | 6629             | 14,610 | 6305             | 13,895 | 6004             | 13,232 |
| <sup>2</sup> 966M   | 9834             | 19,692 | 8478             | 18,685 | 7807             | 17,206 | 6929             | 15,271 | 6208             | 13,682 |
| <sup>2</sup> 972M   | 10108            | 22,279 | 9617             | 21,195 | 9164             | 20,198 | 8743             | 19,270 | 8353             | 18,407 |
| <sup>2</sup> 980M   | 11288            | 24,879 | 9835             | 21,677 | 8689             | 19,150 | 7757             | 17,096 | 6986             | 15,397 |

| 108" Carriage Construction Fork   |                  |        |                  |        |                  |        |                  |        |                  |        |
|---|------------------|--------|------------------|--------|------------------|--------|------------------|--------|------------------|--------|
| Rated Load Firm & Level Ground (80% FTSTL) (Standard Configuration with Fusion) |                  |        |                  |        |                  |        |                  |        |                  |        |
|   | 48" Offset Tines |        | 60" Offset Tines |        | 72" Offset Tines |        | 84" Offset Tines |        | 96" Offset Tines |        |
|   | kg               | lb     | kg               | lb     | kg               | lb     | kg               | lb     | kg               | lb     |
| <sup>1</sup> Fork Capacity (Tine Rating × 2)                                    | 22200            | 48,952 | 17800            | 39,250 | 14800            | 32,634 | 12700            | 28,004 | 11300            | 24,916 |
| <sup>2</sup> 950 GC   | 6374             | 14,049 | 6036             | 13,303 | 5649             | 12,451 | 4995             | 11,009 | 4454             | 9,818  |
| <sup>2</sup> 950M   | 6668             | 14,696 | 6314             | 13,916 | 5986             | 13,193 | 5681             | 12,522 | 5398             | 11,897 |
| <sup>2</sup> 962M   | 7321             | 16,136 | 6948             | 15,313 | 6601             | 14,548 | 6279             | 13,838 | 5978             | 13,175 |
| <sup>2</sup> 966M   | 8902             | 19,620 | 8450             | 18,624 | 7799             | 17,188 | 6922             | 15,256 | 6201             | 13,667 |
| <sup>2</sup> 972M   | 10076            | 22,207 | 9588             | 21,132 | 9136             | 20,136 | 8717             | 19,212 | 8327             | 18,352 |
| <sup>2</sup> 980M   | 11274            | 24,848 | 9826             | 21,353 | 8679             | 19,128 | 7749             | 17,078 | 6978             | 15,380 |

| 980 108" Carriage Construction Fork   |                  |        |                  |        |                  |        |
|---|------------------|--------|------------------|--------|------------------|--------|
| Rated Load Firm & Level Ground (80% FTSTL) (Standard Configuration with Fusion) |                  |        |                  |        |                  |        |
|   | 72" Offset Tines |        | 84" Offset Tines |        | 96" Offset Tines |        |
|   | kg               | lb     | kg               | lb     | kg               | lb     |
| <sup>1</sup> Fork Capacity (Tine Rating × 2)                                    | 18700            | 41,226 | 17716            | 39,056 | 15750            | 34,722 |
| <sup>2</sup> 980M   | 8893             | 19,601 | 7903             | 17,419 | 7031             | 15,496 |

<sup>1</sup>Fork rating is calculated at midpoint of tine.

<sup>2</sup>Some machines have lift capacity that exceeds the rating of the fork. Do not exceed the load capacity of the fork.

